



# LUXOR SLIM

Upright refrigerated display units



Commercial Code	KC6Q
Temperature range	+14/ +16°C
Technical features	<ul style="list-style-type: none"><li>• Display compartment in tempered glass throughout</li><li>• Lower structure in special anti-fingerprintsteel</li><li>• One refrigerated room</li><li>• Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 545 W</li><li>• Climate Class 4, room +30°C and 55% R.H.</li><li>• Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure</li><li>• Relative humidity through humidistat: 40/44%</li><li>• Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain</li><li>• Ventilated system on the back with the air circulation not directed straight at food</li><li>• Refrigerant fluid: R404A</li><li>• Control board with electronic p.c.b. HACCP alarms (high/low temperature, probes failure, open door and black out)</li></ul>
Functional features	<ul style="list-style-type: none"><li>• Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KG: front bearing kit for shelves, to load up to 25 kg</li><li>• Easily removable magnetic gasket</li><li>• Glass door with “invisible” full-height handle</li><li>• Gross internal volume: 324 litri</li><li>• LED lighting</li><li>• Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company</li><li>• Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack</li><li>• Integrated wheels, hidden by the structure. (nr 4)</li></ul>
External size	60x64.5x184cm
Gross/Net weight	171/191kg
Electrical power	0.5 kW Standard connection: V-Hz 230V 1N-/50Hz