



LUXOR

Upright refrigerated display units



Commercial Code	KD8Q
Temperature range	-22/ +5°C
Technical features	<ul style="list-style-type: none">• Display compartment in tempered glass throughout• Lower structure in special anti-fingerprintsteel• A single compartment temperature to positive / negative• Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 1140 W• Climate Class 4, room +30°C and 55% R.H.• Ventilated refrigeration obtained through evaporator fixed in the ceiling of the display compartment by means of an AISI 304 stainless steel structure• Relative humidity: 65/40%• Automatic defrosting by hot gas• Anti-condense heating elements• Ventilated system on the back with the air circulation not directed straight at food• Refrigerant fluid: R404A• Control board with electronic p.c.b. HACCP alarms (high/low temperature, probes failure, open door and black out)
Functional features	<ul style="list-style-type: none">• Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KG: front bearing kit for shelves, to load up to 25 kg• Easily removable magnetic gasket• Glass door with “invisible” full-height handle• Gross internal volume: 490 litri• LED lighting• Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company• Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack• Integrated wheels, hidden by the structure. (nr 4)
External size	80.5x64.5x184cm
Gross/Net weight	232/256kg
Electrical power	1.2 kW Standard connection: V-Hz 230V 1N-/50Hz