







LUXOR BLACK

Upright refrigerated display units





Commercial Code	KG8QA
Temperature range	-25/ -15°C
Technical features	 Display compartment in tempered glass throughout, with black screen-silk printed glass Lower structure in special anti-fingerprint steel black colour A single compartment temperature negative Inner display unit with bottom condense drain hole Cooling unit at evaporation temperature -23.3°C and condensation temperature 53,5°C rated at 1140 W Climate Class 4, room +30°C and 55% R.H. Static refrigeration obtained through the 5 static evaporating grids Relative humidity: 75% Manual stop-system for defrosting Anti-condense heating elements Refrigerant fluid: R404A Black glass electronic panel control board with touch keys and HACCP alarms
Functional features	 Nr 5 evaporating grids + 1 display shelf Easily removable magnetic gasket Glass door with "invisible" full-height handle Gross internal volume: 490 litri High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company Integrated wheels, hidden by the structure. (nr 4)
External size	80.5x64.5x184cm
Gross/Net weight	217/242 kg
Electrical power	1,05 kW Standard connection: V-Hz 230V 1N-/50Hz