



LUXOR BLACK

Upright refrigerated display units



Commercial Code	KP8QA
Temperature range	+2/ +10°C
Technical features	<ul style="list-style-type: none">• Display compartment in tempered glass throughout, with black screen-silk printed glass• Lower structure in special anti-fingerprint steel black colour• One refrigerated room• Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 668 W• Climate Class 4, room +30°C and 55% R.H.• Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure• Relative humidity: 70%• Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain• Ventilated system on the back with the air circulation not directed straight at food• Refrigerant fluid: R404A• Black glass electronic panel control board with touch keys and HACCP alarms
Functional features	<ul style="list-style-type: none">• Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KG: front bearing kit for shelves, to load up to 25 kg• Easily removable magnetic gasket• Glass door with “invisible” full-height handle• Gross internal volume: 490 litri• High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment• Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company• Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack• Integrated wheels, hidden by the structure. (nr 4)
External size	80.5x64.5x184cm
Gross/Net weight	236/211kg
Electrical power	0.65 kW Standard connection: V-Hz 230V 1N-/50Hz